



EN 14592/A1



www.montana.lu

Certificate

Circular ring shank Coil nails for structural timber products

Diameter = 3,8 mm Length = 100-130 mm

Properties of the material used:

- non alloy wire rod in accordance with EN 10016-1 to 4
- tensile strength in accordance with EN 10218-1, min. 700 N/mm²

Characteristic mechanical properties:

- | | |
|-------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------|
| - Yield moment: | $M_{y,k} = 7938 \text{ Nmm}$ |
| - Withdrawal parameter parallel to grain:
Timber: minimum characteristic density of 310 kg/m ³ | $f_{ax,0,k} = 2,75 \text{ N/mm}^2$ |
| - Withdrawal parameter perpendicular to grain:
Timber: minimum characteristic density of 310 kg/m ³ | $f_{ax,90,k} = 6,56 \text{ N/mm}^2$ |
| - Head pull-through parameter:
in OSB/3 with thickness $\geq 9 \text{ mm}$ | $f_{head,k} = 13,93 \text{ N/mm}^2$ |
| - Tensile capacity: | $f_{tens,k} = 7,07 \text{ kN}$ |

Durability (Corrosion Protection):

Bright - Service Class 1 or
Galv < 12 μm Service Class 1 or
Galv 12 μm Service Class 2 acc. to EN1995-1-1